



CM-230A

Part number	Products	Measuring parameters
CM-230A	Conductivity measure instrument with probe and LCD digital display. <b>Probe connection: 1/2"</b> ; <b>Outline dimension: 48x96x100mm</b> Slot dimension for installation: 45x91mm	0-199.9 $\mu\text{S}/\text{cm}^2$
CM-230C	Conductivity measure instrument with probe and LCD digital display. <b>Probe connection: 1/2"</b> ; <b>Outline dimension: 48x96x100mm</b> , Slot dimension for installation: 45x91mm ; Hi-limitid alarm setting	0-199.9 $\mu\text{S}/\text{cm}^2$
CM-230C-GS	Conductivity measure instrument with graphit probe and LCD digital display. <b>Probe connection: 1/2"</b> ; <b>Outline dimension: 48x96x100mm</b> , Slot dimension for installation: 45x91mm ; Hi-limitid alarm setting, See page 67 for more information	0-19.99 $\text{mS}/\text{cm}^2$



ORP/PH



TDS/EC



TDS-2



OKT-1

Part number	Products	Measuring parameters	Numbers of measure
ORP/PH	Digital combined pH and ORP tester, temperature compensated	pH (pH) / ORP (mV)	
PH-CAL/4	20ml Calibration solution of pH 4.01	pH (pH)	
PH-CAL/7	20ml Calibration solution of pH 7.01	pH (pH)	
PH-CAL/10	20ml Calibration solution of pH 10.01	pH (pH)	
PH-STO	230 ml pH sonda storage liquid		
TDS/EC	Conductivity and salt-index tester, temperature compensated	ppm / $\mu\text{S}$	
TDS-2	Digital TDS measurement	Total dissolve solids (ppm)	
OKT-1	Hardness tester, 1 bottle	German hardness ( $^{\circ}\text{dH}$ )	50 pcs
OKT-2	Hardness tester, 2 bottles	German hardness ( $^{\circ}\text{dH}$ )	100 pcs