

2014/ Industrial triplex water softeners

Triplex volume controlled water softener two columns in service one standby

Part number	Resin volume/cap. liter/m ³ x ⁰ dH	Valve / Connection	Brine tank volume (liter)	Flow m ³ /h	Peak flow m ³ /h	Salt cons. kg/reg.	Size(mm) H x W x L	Weight kg
BlueSoft 180T2-RX	3x45 / 3x180	RX-63C-DVS 6/4"	3 x 70	3.6-4.8	8	5.5—10.8	1570 x 710 x 1500	196
BlueSoft 240T2-RX	3x60 / 3x240	RX-63C-DVS 2"	3 x 145	4.8-6.4	8	6—14.4	1590 x 850 x 1530	255
BlueSoft 320T2-RX	3x80 / 3x320	RX-63C-DVS 2"	3 x 145	6.4-7.6	8	8—19.2	1610 x 860 x 1620	323
BlueSoft 400T2-RX	3x100 / 3x400	RX-63C-DVS 2"	3 x 200	7.6-9.0	8	10—24	1930 x 920 x 1710	414
BlueSoft 500T2-RX	3x125 / 3x500	RX-74A-DVS 2"	3 x 200	9.0-11	20	12.5—30	1970 x 970 x 1842	499
BlueSoft 600T2-RX	3x150 / 3x600	RX-74A-DVS 2"	3 x 350	11-14	20	15—36	1980 x 1240 x 2090	614
BlueSoft 800T2-RX	3x200 / 3x800	RX-74A-DVS 3"	3 x 500	14-19	20	20—48	2010 x 1400 x 2300	796
BlueSoft 1200T2-RX	3x300 /3x1200	RX-74A-DVS 3"	3 x 750	19-24	20	30—72	2210 x 1590 x 2450	1 185
BlueSoft 1600T2-RX	3x400 /3x1600	RX-77A-DVS 3"	3 x 750	24-28	36	40—96	2460 x 1750 x 2960	1 720
BlueSoft 1800T2-RX	3x450 /3x1800	RX-77A-DVS 3"	3 x 750	28-34	36	45—108	2460 x 1750 x 2960	1 825
BlueSoft 2400T2-RX	3x600 /3x2400	RX-77A-DVS 3"	3 x 1000	34-36	36	60—144	2470 x 2020 x 3410	2 273
BlueSoft 2600T2-RX	3x650 /3x2600	RX-78SM-DVS DN100	3 x 1000	36—56	80	65—156	2590 x 2720 x 3410	2 543
BlueSoft 2800T2-RX	3x700 /3x2800	RX-78SM-DVS DN100	3 x 1000	56—68	80	70—168	2590 x 2720 x 3410	2 648
BlueSoft 3200T2-RX	3x800 /3x3200	RX-78SM-DVS DN100	3 x 1000	68—80	80	80—192	2590 x 2720 x 3410	2 610

If you need bigger capacity equipment please send your inquiry.



BlueSoft triplex water softener

The advantages of triplex water softeners: every tanks has seperate control valve, the peak flow rate is two times more than the classical duplex (one column in service and one standby) softener. Every time two coloums service the soft water continuously and one column is regenerate or standby.